B	lo	ck	&	B	le	ed	Va	lve
	U	C N	S.			C U	V C	

Hard seat, 316SS, 1/2" NPT 6,000 and 10,000 psi



Overview

Gaugetech[®] Block & Bleed Valves are supplied in 316L stainless steel.

GTHBB series valves are produced with a 1/2" MNPT process connection and female 1/2" NPT instrument connection.

GTHBB series valves are designed with a metal seat for severe working conditions.

All block & bleed valves come standard with a 1/4" NPT side drain port.



Features

- Non-rotating stem plug moves axially into and out of the seat without rotation to eliminate seat galling.
- ▶ The stem threads are rolled and lubricated to prevent galling and reduce operating torque.
- ▶ Valves are assembled with standard t-bar handles.
- All bonnets are assembled with a locking pin to prevent accidental removal while in service.
- ▶ Teflon[®] packing can be adjusted to increase valve life.
- Stem packing below the threads prevents lubricant washout and ensures no process contamination.
- The valves feature safety back seating to ensure a secondary stem seal.

- Dust caps are fitted to contain stem lubricant and prevent the ingreass of contaminants.
- All valves are hydrostatically tested to 1.5 times maximum working pressure prior to shipment.
- The valves are Mill Test Traceable.
- Standard valve on manifold has a 4.8mm orifice size. Cv 0.52 MAX
- ▶ 316SS material traceable to NACE MR0175


AB CRN# 0C08236.2 BC CRN# 0C08236.21 SK CRN# 0C08236.23


How to order

Part Number	Connections		Seat	Material	
	Inlet	Ports			
GTHBB12MFSS	1/2" MNPT	1/2" FNPT	Hard	316SS	
GTHBB12MFSS10	1/2" MNPT	1/2" FNPT	Hard	316SS	
GTHBB12REVFMSS	1/2" FNPT	1/2" MNPT	Hard	316SS	
GTHBB34MFSS10	3/4" MNPT	1/2" FNPT	Hard	316SS	



Dimensions (Drawings are not to scale. Dimensions in millimeters.)








HARD SEAT


No.	Description	SS		
1	Body	S316		
2	Bonnet	S316		
3	Stem	S316		
4	Adjuster	S316		
5	Lock Nut	S316		
6	Handle	S303		
7	Fixing Screw	S302		
8	Packing	Teflon®		
9	Washer	S316		
10	Pusher	S316		
11	Dust cap	NBR		
12	Locking pin	S303		

Dim. Model	А	В	L	Н	H1	W
GTHBB12MFSS	1/2" NPT	32	91	152.5	76.3	57
GTHBB12MFSS10	1/2" NPT	32	91	152.5	76.3	57
GTHBB12REVFMSS	1/2" NPT	32	91	152.5	76.3	57









Pressure vs Temperature Hard Seat

